

Raccordi ad innesto rapido in polimero serie mini

Compact plastic push-in fittings mini serie

Steckverschraubungen Kunststoff Serie mini

Dati tecnici dei raccordi rapidi in polimero serie mini

Compact plastic push-in fittings technical data

Technischen Daten der Steckverschraubungen Kunststoff Serie mini

Fluido Aria compressa (altri fluidi a richiesta)	Fluid Compressed air (other fluids on request)	Fluid Druckluft (andere Medien auf Anfrage)
Pressione di esercizio Tubo Pressione Ø3 – Ø6 mm 0 ÷ 10 Bar 0 ÷ 150 PSI	Working pressure Tube Pressure Ø3 – Ø6 mm 0 ÷ 10 Bar 0 ÷ 150 PSI	Druck Schlauch Druck Ø3 – Ø6 mm 0 ÷ 10 Bar 0 ÷ 150 PSI
Temperatura di utilizzo 0 ÷ 60°C	Temperature range 32 ÷ 140 °F	Einsatztemperatur 0 ÷ 60°C
Tubi consigliati 1)Poliuretano - 2)Poliammide - 3)Polietilene - 4)Nylon	Recommended tubes 1)Polyurethane - 2)Polyamide - 3)Polyethylene - 4)Nylon	Rohrempfehlungen 1) Polyurethan - 2) Polyamid - 3) Polyethylen - 4) Nylon
Tolleranze ± 0.10 mm	Tolerances ± 0.10 mm	Toleranzen ± 0.10 mm
Materiali Corpo: Ottone nichelato o resina acetaleica Pinza: Acciaio SUS 301 Pulsante: Resina acetaleica O-Ring: NBR	Materials Body: Nickel plated brass or acetal resin Lock claws: SUS 301 Steel Sleeve: Acetal resin O-Ring: NBR	Werkstoffen Körper: vernickelt Messing oder Acetal Bremssattel: Stahl SUS 301 Taste: Acetal O-Ringe: NBR
Filettatura BSPP cilindrica - BSPT conica teflonata - Metrica.	Thread types BSPP parallel - BSPT taper with teflon - Metric.	Gewinde BSPP zylindrisch - BSPT konische mit Teflon - Metrische .
Diametri e filetti Diametri da 3 mm a 6 mm - Filettature da M3 a 1/4"	Threads and diameters Diameters from 3 mm to 6 mm - Threads from M3 to 1/4"	Durchmesser und Gewinde Durchmesser von 3 mm bis 6 mm - Gewinde von M3 bis 1/4"
Caratteristiche principali 1. Tenuta al vuoto - 750 mmHG (10Torr) 2. Montaggio istantaneo 3. Passaggio pieno, nessuna riduzione della portata 4. Ingombri ottimizzati	Main features 1. Vacuum - 750 mmHG (10Torr) 2. Instant connection 3. Full passage, no reduction flow 4. Optimized dimensions	Haupteigenschaften 1. Vakuumdichtigkeit - 750 mmHG (10Torr) 2. Sofortige Installation 3. Voller Durchgang, keine Reduktion im Umfang 4. Optimierte Abmessungen


RP 51K-C



Diritto compatto maschio conico BSPT-metrico

Mini male straight taper BSPT-metric
Gerade Einschraubverschraubung konisches Gewinde "MINI"

Codice/Code	ØD	R"	L1	L2	Ø	h			
RP51M303C	3	M3X0.5	3.5	15		8			10
RP51M503C	3	M5X0.8	3.5	16	2	8			10
RP51K1803C	3	R1/8	7.5	15	2	10			10
RP51M304C	4	M3X0.5	3.5	17.5		8			10
RP51M504C	4	M5X0.8	3.5	18.5	2	8			10
RP51M604C	4	M6X1.0	4	19	2	10			10
RP51K1804C	4	R1/8	7.5	16	3	10			10
RP51K1404C	4	R1/4	9.5	18	3	14			10
RP51M506C	6	M5X0.8	3.5	18	2	10			10
RP51M606C	6	M6X1.0	4	18.5	2	10			10
RP51K1806C	6	R1/8	7.5	18.5	4	10			10




RP 51-C



Diritto compatto maschio cilindrico BSPP

Mini male straight parallel BSPP
Gerade Einschraubverschraubung zylindrisches Gewinde "MINI"

Codice/Code	ØD	R"	L1	L2	Ø	h			
RP511804C	4	G1/8	5.5	15.2	3	14			10
RP511404C	4	G1/4	7.5	17.2	3	17			10
RP511806C	6	G1/8	5	17.2	4	13			10
RP511406C	6	G1/4	7.5	18.5	4	17			10




RP 51T-C



Diritto compatto tondo maschio conico BSPT-metrico

Mini round male straight taper BSPT-metric
Rund Gerade Einschraubverschraubung konisches Gewinde "MINI"

Codice/Code	ØD	R"	L1	L2	ØD1	Ø	ØD2		
RP51TM303C	3	M3X0.5	3.5	15	6.5		7.5		10
RP51TM503C	3	M5X0.8	3.5	16	8	2	7.5		10
RP51TM304C	4	M3X0.5	3.5	17.5	8		10		10
RP51TM504C	4	M5X0.8	3.5	18	8	2	10		10
RP51TM604C	4	M6X1.0	4	18.5	8	2	10		10
RP51TK1804C	4	R1/8	7.5	15.5	10	3	10		10
RP51TM506C	6	M5X0.8	3.5	18	10	2	11.5		10
RP51TM606C	6	M6X1.0	4	18.5	10	2	11.5		10
RP51TK1806C	6	R1/8	7.5	18.5	10	4	11.5		10




RP 53-C



Diritto intermedio compatto

Mini straight intermediate
Gerader Verbinder "MINI"

Codice/Code	ØD	ØD1	L						
RP530003C	3	7.5	21						10
RP530004C	4	9.5	26.5						10
RP530006C	6	11.5	27.5						10



Raccordi ad innesto rapido in polimero serie mini

Compact plastic push-in fittings mini serie

Steckverschraubungen Kunststoff Serie mini


RP 54-C



L intermedio compatto

Mini elbow intermediate
Winkelverbinder "MINI"

Codice/Code	ØD	ØD1	ØD2	L1	L2				
RP540003C	3	7.5	3.2	12	4.8				10
RP540004C	4	9.5	3.2	14.5	6				10
RP540006C	6	11.5	3.2	16	6.5				10




RP 55-C



T intermedio compatto

Mini T intermediate
T Verbinder "MINI"

Codice/Code	ØD	ØD1	ØD2	L1	L2	L3	L4		
RP550003C	3	7.5	3.2	23.5	9.6	11.8	4.8		10
RP550004C	4	9.5	3.2	29	12	14.5	6		10
RP550006C	6	11.5	3.2	32	13	16	6.5		10




RP 70-C



T al centro compatto girevole conico BSPT-metrico

Mini central T male (rotating body) taper BSPT-metric
T-Einschraubverschraubung Drehbar, konisches Gewinde "MINI"

Codice/Code	ØD	R"	L1	L2	L3	ØD1			
RP70M303C	3	M3X0.5	3.5	16	24	7.5	8		10
RP70M503C	3	M5X0.8	3.5	16	24	7.5	8		10
RP70K1803C	3	R1/8	7.5	16.5	24	7.5	10		10
RP70M304C	4	M3X0.5	3.5	17.2	28	9.5	8		10
RP70M504C	4	M5X0.8	3.5	17.2	28	9.5	8		10
RP70M604C	4	M6X1.0	4	17.6	28	9.5	10		10
RP70K1804C	4	R1/8	7.5	18	28	9.5	10		10
RP70M506C	6	M5X0.8	3.5	18.2	32	11.5	8		10
RP70M606C	6	M6X1.0	4	18.6	32	11.5	10		10
RP70K1806C	6	R1/8	7.5	19	32	11.5	10		10




RP 71-C



T laterale compatto girevole conico BSPT-metrico

Mini lateral T male (rotating body) taper BSPT-metric
T-Verschraubung Drehbar, konisches Gewinde "MINI"

Codice/Code	ØD	R"	L1	L2	L3	ØD1			
RP71M303C	3	M3X0.5	3.5	16	12	7.5	8		10
RP71M503C	3	M5X0.8	3.5	16	12	7.5	8		10
RP71K1803C	3	R1/8	7.5	16.5	12	7.5	10		10
RP71M304C	4	M3X0.5	3.5	17.2	14	9.5	8		10
RP71M504C	4	M5X0.8	3.5	17.2	14	9.5	8		10
RP71M604C	4	M6X1.0	4	17.6	14	9.5	10		10
RP71K1804C	4	R1/8	7.5	18	14	9.5	10		10
RP71M506C	6	M5X0.8	3.5	18.2	14.5	11.5	8		10
RP71M606C	6	M6X1.0	4	18.6	14.5	11.5	10		10
RP71K1806C	6	R1/8	7.5	19	14.5	11.5	10		10




RP 72K-C



Gomito compatto maschio girevole conico BSPT-metrico

Mini elbow male (rotating body) taper BSPT-metric
Winkelverschraubung Drehbar, konisches Gewinde "MINI"

Codice/Code	ØD	R"	L1	L2	L3	ØD1			
RP72M303C	3	M3X0.5	3.5	16	12	7.5	8		10
RP72M503C	3	M5X0.8	3.5	16	12	7.5	8		10
RP72K1803C	3	R1/8	7.5	16.5	12	7.5	10		10
RP72M304C	4	M3X0.5	3.5	17.2	14	9.5	8		10
RP72M504C	4	M5X0.8	3.5	17.2	14	9.5	8		10
RP72M604C	4	M6X1.0	4	17.6	14	9.5	10		10
RP72K1804C	4	R1/8	7.5	18	14	9.5	10		10
RP72M506C	6	M5X0.8	3.5	17.2	16	11.5	8		10
RP72M606C	6	M6X1.0	4	17.6	16	11.5	10		10
RP72K1806C	6	R1/8	7.5	18	16	11.5	10		10



RP 72 -C



Gomito compatto maschio girevole cilindrico BSPP

Mini elbow male (rotating body) parallel BSPP
Winkelverschraubung Drehbar zylindrisches Gewinde "MINI"

Codice/Code	ØD	R"	L1	L2	L3	ØD1			
RP721804C	4	G1/8	5.5	16.5	14	9.5	14		10
RP721404C	4	G1/4	7.5	19.5	14	9.5	17		10
RP721806C	6	G1/8	5.5	16.5	16	11.5	14		10
RP721406C	6	G1/4	7.5	19.5	16	11.5	17		10

