

Valvole e rubinetti in ottone

Brass valves

Messing Kugelhähne

Dati tecnici valvole di sicurezza RV 10-11

Safety valve RV 10-11 technical data

Technischen Daten der Sicherungshähne RV 10-11

Caratteristiche tecniche

Corpo: OT58 UNI EN 12164
Otturatore: OT58 UNI EN 12164
Sede: OT58 UNI EN 12164
Spillo: OT58 UNI EN 12164
Guarnizione: NBR-VITON
Molla: C98 UNI 3823 INOX AISI 302

Technical data

Body: OT58 UNI EN 12164
Spear valve: OT58 UNI EN 12164
Seat: OT58 UNI EN 12164
Needle: OT58 UNI EN 12164
Washer: NBR-VITON
Spring: C98 UNI 3823 INOX AISI 302

Technischen Daten

Gehäuse: OT58 UNI EN 12164
Blende: OT58 UNI EN 12164
Sitz: OT58 UNI EN 12164
Nadel: OT58 UNI EN 12164
Dichtung: NBR-VITON
Feder: C98 UNI 3823 INOX AISI 302

Diametro orificio

1/8" - 1/4" 6 mm
3/8" 10 mm
1/2" 11 mm
3/4" 13 mm
1" 15 mm

Orifice Diameter

1/8" - 1/4" 6 mm
3/8" 10 mm
1/2" 11 mm
3/4" 13 mm
1" 15 mm

Ø Öffnung

1/8" - 1/4" 6 mm
3/8" 10 mm
1/2" 11 mm
3/4" 13 mm
1" 15 mm

Area orificio

1/8" - 1/4" 28,26 mm²
3/8" 78,5 mm²
1/2" 94,9 mm²
3/4" 132,6 mm²
1" 176,6 mm²

Orifice Area

1/8" - 1/4" 28,26 mm²
3/8" 78,5 mm²
1/2" 94,9 mm²
3/4" 132,6 mm²
1" 176,6 mm²

Fläche

1/8" - 1/4" 28,26 mm²
3/8" 78,5 mm²
1/2" 94,9 mm²
3/4" 132,6 mm²
1" 176,6 mm²

Temperatura di esercizio

NBR: -10 °C ÷ +90 °C
VITON: -10 °C ÷ +250 °C

Working temperature

NBR: -10 °C ÷ +90 °C
VITON: -10 °C ÷ +250 °C

Betriebstemperatur

NBR: -10 °C ÷ +90 °C
VITON: -10 °C ÷ +250 °C

Campo di taratura

0 ÷ 18 bar

Setting range

0 ÷ 18 bar

Regulierbereich

0 ÷ 18 bar

Portata effettiva di scarico l/m - Real flow of blowdown lt/m - Effektiver abflussdurchsatz lt/m

BAR	1/8" - 1/4"	3/8"	1/2"	3/4"	1"
1	130	405	449	3572	5946
2	167	550	610	4601	7004
3	350	786	872	5630	8054
4	550	1150	1276	6659	9304
5	920	1850	2053	7688	10554
6	1300	2458	2728	8717	11534
7	1630	3350	3718	10220	12542
8	2500	4300	5413	11728	13492
9	2800	4765	5765	12757	15618
10	3316	5960	6344	13786	16576
11	3450	6871	7626	14815	17857
12	3600	7836	8768	15844	19138
13	3807	9487	10530	16873	20419
14	3904	9758	10831	17902	21700
15	4100	10180	11299	18755	22981
16	4450	11287	12528	19608	24262
17	4700	12468	12700	20461	25543
18	4850	12780	13950	21314	26545

RV 10



Valvola sicurezza tarata

Set safety valve
Überdruckventil

Codice/Code	Misure/Size	Tarata/Set	
RV100814	G1/4"	8,5 BAR	1
RV101238	G3/8"	12 BAR	1
RV101212	G1/2"	12 BAR	1
RV101234	G3/4"	12 BAR	1
RV101201	G1"	12 BAR	1

RV 11



Valvola sicurezza libera

Free safety valve
Überdruckventil

Codice/Code	Misure/Size		
RV110018	G1/8"	1	1
RV110014	G1/4"	1	1
RV110038	G3/8"	1	1
RV110012	G1/2"	1	1

RV 28



Rubinetto spurgo

Draing valve
Entlüftungsventil

Codice/Code	Misure/Size		
RV280018	G1/8		10
RV280014	G1/4		10
RV280038	G3/8		10
RV280012	G1/2		10


RV 33



Rubinetto linea con volantino ghiera

Male line valve
Ventil

Codice/Code	F	F1	I	H	L	L1	CH	M	
RV330014	1/4	1/4	11	44,5	59,5	21	15	45	10
RV330038	3/8	1/4	11,5	44,5	59,5	20,5	15	45	10
RV330012	1/2	1/4	12,5	44,5	63,5	23,5	22	45	10



RV 34



Rubinetto linea levetta ghiera

Male line valve
Ventil

Codice/Code	F	F1	I	H	L	L1	CH	M	
RV340018	1/8	1/4	9	37,5	46,5	16	13	34	10
RV340014	1/4	1/4	11	44	59,5	21	15	43	10
RV340038	3/8	1/4	11,5	44	59,5	20,5	15	43	10
RV340012	1/2	1/4	12,5	44	63,5	23,5	22	43	10

