

Valvole e rubinetti in ottone

Brass valves

Messing Kugelhähne

Dati tecnici valvole di scarico rapido RV 40-40P-40G

Exhaust valves RV 40-40P-40G technical data

Technischen Daten der Schnellentlüftungsventil RV 40-40P-40G

Applicazioni

Circuiti pneumatici

Applications

Pneumatic systems

Anwendungen

Pneumatikkreisläufe

Pressione

Min. 0,3 BAR / max. 10 BAR

Pressure

Min. 0,3 BAR / max. 10 BAR

Druck

Min. 0,3 BAR / max. 10 BAR

Temperatura

Min. -20°C / max. +80°C

Temperature

Min. -4°F / max. 176°F

Temperatur

Min. -20°C / max. +80°C

Materiali

Corpo/Tappo: ottone UNI EN 12165 CW617N
Elemento di tenuta: Elastomero poliuretano
Guarnizione tenuta corpo/tappo: Nylon

Materials

Body/cap: Brass UNI EN 12165 CW 617N
Sealing element: Polyurethane elastomer
Body/cap seal: Nylon

Werkstoffen

Gehäuse/Kappe: Messing UNI EN 12165 CW 617N
Dichtungen: Polyurethan Elastomer
Dichtung Gehäuse/Kappe: Nylon

Trattamento superficiale

Nichelatura

Surface treatment

Nickel-plating

Oberflächenbehandlung

Nickel

Filettatura

Gas cilindrica ISO 228 (BSPP)

Thread

Cylindrical GAS ISO 228 (BSPP)

Gewinde

Gas zylindrisch ISO 228 (BSPP)

RV 40




Valvola di scarico rapido

Quick exhaust valve

Schnellentlüftungsventile

Codice/Code	F"	I	H	H1	CH	CH1	E	
RV4000M5	M5	4,5	24,8	15,6	10	10	10,5	10
RV400018	1/8	8	42	28	14	14	19,5	10
RV400014	1/4	11	53	34,5	19	19	25	10
RV400038	3/8	12	58	36	21	21	26	10
RV400012	1/2	14	71	44	26	26	35	5
RV400034	3/4	18	86	52	32	32	38,5	5
RV400001	1	19	94	56	38	38	42	5



RV 40P




Membrana per valvola di scarico rapido

Membrane for quick exhaust valve

Membrane für Schnellentlüftungsventile

Codice/Code	A	B					
RV40PM5	13,5	4,5					1
RV40P18	20,5	5					1
RV40P1438	25,5	5,8					1
RV40P12	35,5	8,2					1
RV40P3401	40,5	9					1



RV 40G



Guarnizione in nylon per valvola di scarico rapido

Nylon seal for quick exhaust valve

Dichtung Nylon für Schnellentlüftungsventile

Codice/Code	A	B	C				
RV40GM5	17	12,4	0,8				1
RV40G18	23,8	20	1				1
RV40G1438	28,5	24	1				1
RV40G12	38,6	32	1,5				1
RV40G3401	45	38	1,5				1

